

# RESULTS THAT JUMP OFF THE PAGE & BOOST EFFICIENCY

Canon imageRUNNER ADVANCE

## C3500i Series



The imageRUNNER ADVANCE C3500i series introduces a new dynamic to printing technology with 20/30ppm speed options, a compact footprint, and vivid colour results. This new edition to the GEN III platform is built with both the user and medium-sized offices in mind.

- Compact A3 Colour multifunction device
- Prints up to 30 ppm in colour
- Vivid & Vibrant V2 Colour
- Built in WiFi



### PERFORMANCE

Manage your projects with ease thanks to an intuitive design and advanced printing capabilities

- A3 mid- to low-volume colour device with two speeds
- 10.1 inch full colour WVGA LCD display (touchscreen) with recently updated user interface
- Vivid and vibrant colour delivers a crisp, even finish
- Space-saving Inner Finisher incorporates ECO-Staple, Staple, and Staple-On-Demand functionalities
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs



### INTEGRATION

Seamlessly integrate with key line-of-business systems

- Seamlessly integrate with key line-of-business systems to power your digital transformation journey
- Collaborate with key line of business applications and external systems
- Personalised workflows give users the ability to take control of the way they want to manage their information so that it works best for them
- Leverage Canon's Multifunctional Embedded Application Platform (MEAP) to optimise processes with a range of powerful document, capture and output management solutions



### COST CONTROL

Streamline workflows while managing costs

- Forced Job Hold ensures secure printing for each user
- Ability to change print settings at the device allows for extra control over jobs
- Blank page removal comes standard and works to reduce paper wastage



### MOBILITY

Workers and contractors can achieve ultimate freedom and flexibility with Expanded Mobile OS Support

- Mobile workflows are set up with built in WiFi and mobile applications to easily allow users to connect, print, scan and capture using Canon PRINT Business
- Full support for Apple Airprint and Android Mopria Mobile Printing
- Simple and easy mobile connectivity with standard in-built WiFi

 **SUSTAINABILITY**

Designed to help achieve environmental goals

- Motion sensors and sleep recovery triggers work to reduce unnecessary power consumption
- Bio-based plastics are used throughout the machine for an environmentally friendly approach to printing performance

 **SECURITY**

Safeguard data and ensure sensitive information remains secure

- Standard HDD Encryption works to prevent data leaks and keep confidential information protected
- Security settings have been consolidated to reduce administration
- Security policy support is also available

# CONFIGURATION



# imageRUNNER ADVANCE C3500i Series

## Main Unit

Type	Colour Laser Multifunction
Core Function	Print, Copy, Scan, Send, Store and Optional Fax
Processor	Canon Dual Custom Processor (Shared)
Control Panel	10.1 inch TFT LCD WSVGA Colour Touchpanel
Memory	Standard: 3.0GB RAM
Hard Disk Drive	Standard: 250GB Maximum: 1TB
Mirroring Hard Disk Drive	Optional 1TB
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n), Optional: NFC, Bluetooth Others: Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device), Optional: Serial Interface, Copy Control Interface
Paper Capacity (A4, 80gsm)	Standard: 1,200 Sheets Maximum: 2,300 Sheets
Paper Sources (A4, 80gsm)	Standard: Two 550-sheet Paper Cassettes, 100-sheet Multi-purpose Tray Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AP1) Maximum: 2,300 Sheets
Paper Output Capacity (A4, 80gsm)	Standard: 250 Sheets Maximum: 3,450 Sheets (with External Finisher/Copy Tray)
Finishing Capabilities	Standard: Collate, Group With Inner Finisher: Collate, Group, Offset, Staple, Staple-Free Staple, Staple On Demand With External Finisher: Collate, Group, Offset, Staple, *Booklet, *Hole Punch, Staple-Free Staple, Staple On Demand *Necessary for 2/3/4 Hole Puncher Unit-A1 **Necessary for Booklet Finisher-AA1 only
Supported Media Types	Cassettes 1/2: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Bond paper, Envelope Multi-purpose tray: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Tracing paper, Label, Bond paper, Coated paper, Envelope Cassettes 3/4 (Cassette Feeding Unit-AP1): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Bond paper
Supported Media Sizes	Cassette 1: Standard Size: A4, B5, A5R, Envelopes: No.10 (COM10), ISO-C5, DL, Custom Size: 139.7 mm x 182 mm to 297 mm x 215.9 mm Cassette 2: Standard Size: A3, B4, A4, B5, A4R, A5R, Envelopes: No.10 (COM10), Monarch, DL, Custom Size: 139.7 mm x 182 mm to 304.8 x 457.2 mm Cassette 3/4 (Cassette Feeding Unit-AN1): Standard Size: A3, B4, A4, A4R, B5R, B5, A5R, Custom Size: 139.7 mm x 182 mm to 304.8 mm x 457.2 mm Multi-purpose tray: Standard Size: A3, B4, A4, A4R, B5R, B5, A5, A5R, SRA3, Custom Size: 98.4 mm x 139.7 mm to 320 mm x 457.2 mm, Free Size: 98.4 mm x 139.7 mm to 320 mm x 457.2 mm, Envelopes: No.10 (COM10), Monarch, ISO-C5, DL, Envelope Custom Size: 98 mm x 98 mm to 320 mm x 457.2 mm
Supported Media Weights	Cassette 1, 2: 52 to 220 gsm Cassette Feeding Unit: 52 to 220 gsm Multi-purpose tray: 52 to 300 gsm Duplex: 52 to 220 gsm
Warm-up Time	From Power On: 34 Seconds or Less (Time between device power-on and when the start key is enabled (print reservation) Quick startup Mode ON) From Deep Sleep Mode: 10 Seconds or Less Quick Startup Mode: 10 Seconds or Less
Dimensions (W x D x H)	565 mm x 742 mm x 900 mm
Installation Space (W x D)	Basic: 978 mm x 1123 mm (when attach with Multi-purpose tray open + Cassette Drawers open) Fully Configured: 1620 mm x 1123 mm (when attach with Booklet Finisher-AA1 + Multi-purpose tray extension extended)
Weight*	Approx. 81.5kg (when attach with Single Pass DADF-A1) *Including the toner bottle

## Print Specifications

Printing Method	Colour laser beam printing
Print Speed	IR-ADV C3530i: 30 ppm (A4), 15 ppm (A3), 20 ppm (A4R), 30 ppm (A5R) IR-ADV C3520i: 20 ppm (A4), 15 ppm (A3), 20 ppm (A4R), 20 ppm (A5R)
Print Resolution*	Engine resolution: 600 dpi x 600 dpi, 1200 dpi x 1200 dpi Laser resolution: 9600 dpi equivalent x 600 dpi (600 dpi mode) / 1200 dpi x 1200 dpi (1200 dpi mode) *Laser Resolution
Page Description Languages	UFR II, PCL6, Adobe PS 3 (Option)
Direct Print	Direct printing available from USB memory key, Advanced box, Remote UI and Web Access (Only PDF print from websites is supported.) Supported File Types: PDF, TIFF, JPEG, EPS, XPS
Printing from Mobile and Cloud	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices. Please contact your sales representative for further information.
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts** *Requires optional PCL International Font Set-A1 **Require optional Barcode PRT Kit-D1 PS fonts: 136 Roman
Print Features	Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing
Operating System	UFR II: Windows Vista/Server 2008/Windows 7/Server 2008 R2/ Windows 8/Server 2012/Windows 8.1/Server 2012 R2/ Windows 10/ Server 2016, MAC OS X (10.7 or later) PCL: Windows Vista/Server 2008/Windows 7/Server 2008 R2/ Windows 8/Server 2012/Windows 8.1/Server 2012 R2/ Windows 10/ Server 2016 PS: Windows Vista/Server 2008/Windows 7/Server 2008 R2/ Windows 8/Server 2012/Windows 8.1/Server 2012 R2/ Windows 10/Server 2016, MAC OS X (10.7 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 10

## Copy Specifications

Copy Speed	IR-ADV C3530i: 30 ppm (A4), 15 ppm (A3), 20 ppm (A4R), 30 ppm (A5R) IR-ADV C3520i: 20 ppm (A4), 15 ppm (A3), 20 ppm (A4R), 20 ppm (A5R)
*First-Copy-Out Time (A4)	Approx. 5.9 seconds or less (BW), Approx. 8.2 seconds or less (CL) *20 °C to 30 °C Environment

Copy Resolution	Reading: 600 dpi x 600 dpi Printing: Up to 1200 dpi x 1200 dpi
Multiple Copies	Up to 999 copies
Copy Exposure	Automatic or Manual (11 Levels)
Magnification	25% - 400% (1% Increments)
Preset Reductions	25%, 50%, 61%, 70%, 81%, 86%
Preset Enlargements	115%, 122%, 141%, 200%, 400%
Basic Copy Features	Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favourite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel
Special Copy Features	Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Store in Mail Box, Superimpose Image, Cascade Copy, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original

## Scan Specifications

Type	Single-pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity	150 Sheets (80 gsm)
Document Feeder Supported Media Sizes	A3, B4, A4, A4R, B5, B5R, A5, A5R, B6R
Document Feeder Supported Media Weights	Single-sided scanning: 38 to 157 gsm (BW) Single-sided scanning: 64 to 157 gsm (CL) Double-sided scanning: 50 to 157 gsm (BW) Double-sided scanning: 64 to 157 gsm (CL)
Pull Scan Spec	Color Network ScanGear2. For both Twain and WIA Supported OS: Windows Vista/7/8/8.1/10, Windows Server 2008/ Server 2008 R2/Server 2012/Server 2012 R2
Scan Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Platen Acceptable Originals	Platen: Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2kg)] Paper Size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6
Scan Method	Send functionality available on all models Scan to USB Memory Key: Available on all models Scan to Mobiles or internet-connected devices: A range of solutions is available to provide scanning to mobile devices or internet-connected devices depending on your requirements. Please contact your sales representative for further information. TWAIN/WIA Pull scanning available on all models
Scan Speed (A4)	Single-sided Scanning (BW): 80 ipm (300pi) / 51 ipm (600 dpi) Single-sided Scanning (CL): 80 ipm (300pi) / 51 ipm (600 dpi) Double-sided Scanning (BW): 160 ipm (300pi) / 51 ipm (600 dpi) Double-sided Scanning (CL): 160 ipm (300pi) / 51 ipm (600 dpi)

## Send Specifications

Optional/Standard	Standard on all models
Destination	E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)
Colour Mode	Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full Colour, Grayscale, and Black-and-White
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Communication Protocol	File: FTP, SMB v3.0, WebDAV, E-mail/Internet Fax: SMTP, POP3, I-Fax (Simple, Full)
File Format	Standard: TIFF, JPEG, PDF (Compact, Apply policy, Optimise for Web, PDF A/1-b) Optional: PDF (Searchable, Trace&Smooth, Encrypted), PDF/XPS (Digital Signature), XPS (Searchable), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed.

## Fax Specifications

Optional/Standard	Optional on all models
Maximum Number of Connection Lines	2
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi
Sending/Recording Size	A5* and A5R* to A3* (Sent as A4)
Fax Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
Fax Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending Fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending Fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed.

## Store Specifications

Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)
Advanced Box Available Disc Space	Approx. 16GB (Standard HDD) Approx. 480GB (1TB HDD)
Advanced Box Features	Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support
Memory Media	Standard: USB Memory

## Security Specifications

Authentication	Standard: Picture Login Authentication, DepartmentID Authentication, (Device and Function Level Login), Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW)
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated) Optional: Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

## Environmental Specifications

Operating Environment	Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80 % RH (no condensation)
Power Requirements	220-240V(±10 %), 50/60Hz (±2 Hz), 4.0Amp
Power Consumption	Maximum: 1.5 kW Standby: Approx. 41.2 Wh* *Reference Value Sleep mode: Approx. 0.8 W** **0.8W sleep mode is not available in all circumstances due to certain settings. Typical Electricity Consumption (TEC) rating 1.2 kWh (iR-ADV C3530) 0.8 kWh (iR-ADV C3520)
Standards	ENERGY STAR® Qualified, Rated EPEAT (Gold), Blue Angel

## Consumables

Toner	NPG-67 TONER BK/C/M/Y
-------	-----------------------

## Software and Printer Management

Remote Management Tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, IR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Scanning Software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	iW Desktop: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.

## Paper Supply Options

Name	Cassette Feeding Unit-AP1
Paper Capacity	550 Sheets x 2 Cassettes (80 gsm)
Paper Size	A3, B4, A4, A4R, B5R, B5, A5R Custom Size: 139.7 mm x 182.0 mm to 304.8 mm x 457.2 mm
Paper Weight	52 to 220 gsm
Power Source	From the Main Unit / Include in the Energy Consumption of main body
Dimensions (W x D x H)	565 mm x 615 mm x 248 mm (When attached with the Main Unit)
Weight	Approx. 16 kg

## Output Options

Name	Inner 2Way Tray-L1
Number of Trays	2
Total Output Capacity	Upper Tray: 100 sheets Lower Tray: 250 sheets
Paper Weight	52 to 300 gsm
Paper Size	A3, B4R, A4, B5, A5, A4R, B5R, A5R, Custom Size: 98.4 mm x 139.7 mm up to 320 mm x 457.2 mm Free Size: 98.4 mm x 139.7 mm up to 320mm x 457.2 mm, Envelope (No.10 (COM10), Monarch, DL, ISO-C5), Envelope Custom Size: 98.0 mm x 98.0 mm up to 320 mm x 457.2 mm
Dimensions (W x D x H)	427 mm x 407 mm x 76 mm (When attached with the Main Unit)
Weight	Approx. 0.6 kg
Name	Inner Shift Sorter-A1
Number of Trays	1
Total Output Capacity	A4/B5: 250 sheets, A3/B4R/A4R/A5/A5R/B5R: 125 sheets
Paper Weight	52 to 300 gsm
Dimensions (W x D x H)	538 mm x 523 mm x 114 mm (When the extension tray is extended)
Weight	Approx. 3.0 kg

Name	Inner Finisher-K1
Number of Trays	2
Top Tray Capacity	A4, B5, A5, A5R 100 sheets, A3, B4, A4R, B5R, SRA3 50 sheets
Lower Tray Capacity	A4, B5, A5, A5R 500 sheets, A3, B4, A4R, B5R, SRA3 250 sheets
Paper Weight	52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 50 sheets (52 to 90 gsm), A3/B4/A4R: 30 sheets (52 to 90 gsm) Staple-Free Staple: A3/A4/B4/B5: 5 sheets (52 to 64 gsm), 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 40 sheets (80 gsm)

Power Source	From the Main Unit
Dimensions (W x D x H)	604 mm x 525 mm x 188 mm (When the extension tray is extended)
Weight	Approx. 8 kg

Name	Staple Finisher-AA1 (External)
Number of Trays	2
Top Tray Capacity	A4, B5, A5, A5R 250 sheets, A3, B4, A4R, B5R, SRA3 125 sheets
Lower Tray Capacity	A4, B5, A5, A5R 3,000 sheets, A3, B4, A4R, B5R, SRA3 1,500 sheets
Paper Weight	Top Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 50 sheets (52 to 90 gsm), A3/B4/A4R: 30 sheets (52 to 90 gsm) Staple-Free Staple: A3/A4: 5 sheets (52 to 64 gsm), 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)

Power Source	From the Main Unit
Dimensions (W x D x H)	637 mm x 623 mm x 1,016 mm (When the extension tray is extended)
Weight	Approx. 30 kg

Name	Booklet Finisher-AA1 (External)
Number of Trays	2
Top Tray Capacity	A4, B5, A5, A5R 250 sheets, A3, B4, A4R, B5R, SRA3 125 sheets
Lower Tray Capacity	A4, B5, A5, A5R 3,000 sheets, A3, B4, A4R, B5R, SRA3 1,500 sheets
Paper Weight	Top Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 50 sheets (90 gsm), A3/B4/A4R: 30 sheets (90 gsm) Staple-Free Staple: A3/A4: 5 sheets (52 to 64 gsm), 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)

Booklet Stitch Paper Size	A3, B4, A4R, Custom Size (195.0 mm x 270 mm to 304.8 mm x 457.2 mm)
Booklet Stitch Staple Capacity	20 sheets x 10 sets (81 gsm) (Including 1 cover sheet up to 256 gsm)
Power Source	From the Main Unit
Dimensions (W x D x H)	637 mm x 623 mm x 1,016 mm (When the extension tray is extended)
Weight	Approx. 53 kg

Name	2/3 Hole Puncher Unit-A1, Two or Three Holes *Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4R, A4, A4R, B5, B5R, Three holes: A3, B4R, A4, B5
Power Source	From the Main Unit
Name	2/4 Hole Puncher Unit-A1: Two or Four Holes *Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4R, A4, A4R, B5, B5R, Four holes: A3, A4
Power Source	From the Main Unit

## Hardware Accessories

Card Readers	MiCard Plus Proximity Card Reader
Others	Utility Tray-B1

## Security Options

Document Security	Document Scan Lock Kit-B1, Secure Watermark-B1, Encrypted Secure Print Software-D1
Data Security	2.5inch/1TB HDD-P1, Removable HDD Kit-AK2

## System and Controller Options

Print Accessories	PCL International Font Set-A1
Barcode Printing	Barcode Printing Kit-D1
System Accessories	Web Access Software-K1, Serial Interface Kit-K3
Fax Accessories	Super G3 Fax Board-AU1, Super G3 2nd Line Fax Board-AU1, Remote Fax Kit-A1, IP Fax Expansion Kit-B1

## Other Options

Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Stamp Ink Cartridge-C1, Stamp Unit-B1, Staple-P1, Staple Cartridge-Y1

canon.com.au/business

Follow us on Twitter @CanonBusinessAU

1800 444 199

**Canon**

*achieve more.*